



Strojirenský zkušební ústav, s.p.
(Engineering Test Institute, Public Enterprise)
Hudcova 424/56b, Mediánky, 621 00 Brno, Czech Republic
Notified body 1015

CERTIFICATE OF CONFORMITY OF THE FACTORY PRODUCTION CONTROL

1015-CPR-E-30-20507-17 rev.1

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

**Cold formed welded structural hollow sections of non-alloy steels
according to EN 10219-1:2006**

**Circular Hollow Sections
Square Hollow Sections
Rectangular Hollow Sections
Steel Quality / Steel Grade: S235, S355, S275**

Construction products parameters: see Annex 1 (page 2)

placed on the market under
the name or trade mark of:

**LONGOFER
R.N. 9 Km. 10 – Ahl Loghlam
20640 – Tit Mellil
Casablanca, Morocco**

and produced in the
manufacturing plant:

**LONGOFER
R.N. 9 Km. 10 – Ahl Loghlam
20640 – Tit Mellil
Casablanca, Morocco**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 10219-1:2006

under system 2+ are applied and that the factory production control is assessed to be in conformity with the applicable requirements.

This certificate was first issued on 2017-10-20 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

Basis of Certificate issuance: **Final Report 30-15716/JZ of 2021-12-15**

Brno, 2021-12-15




.....
Ing. Pavel Štícha
Director for Certification





Certificate of conformity of the factory production control 1015-CPR-E-30-20507-17 rev.1
Annex 1

Cold formed welded structural hollow sections of non-alloy steels
according to EN 10219-1:2006

Size range:

Circular Hollow Sections, outside diameter (D): from (21,3 to 2500) mm

Wall thickness range: from (2,0 to 30,0) mm

Square Hollow Sections: from (20x20) mm to (260x260) mm

Rectangular Hollow Sections: from (40x20) mm to (300x260) mm

Wall thickness range: from (2,0 to 12,0) mm

Steel Quality / Steel Grade: S235, S355, S275

Tolerances, dimensions and sectional properties: according to EN 10219-2:2006.

Application (Intended use): To be used in metal structures or in composite metal and concrete structures for building and civil engineering.

